

BPIR DECLARATION

Version 1.1 September 2024

DESIGNATED BUILDING PRODUCT: Class 1

DECLARATION

J Scott & Company Ltd t/a JSC has provided this declaration to satisfy the provisions of the [Building \(Building Product Information Requirements\) Regulations 2022](#).

COMPANY DETAILS

Name	J Scott & Company Ltd t/a JSC
Role	Manufacturer
NZBN	9429039389657
Address	22 Sawmill Rd, Riverhead, Auckland
Website	www.jsc.co.nz
Email	sales@jsc.co.nz
Phone	0800 57 26 88

DESCRIPTION OF BUILDING PRODUCT

JSC supplies proprietary timber cavity battens for use in external cladding applications. They are treated to H3.2 (MCA or CCA), come with bevelled top and bottom edges and larger castellations which improves water management within a ventilated cavity. Treatment to H3.2 allows for JSC to claim a durability of 50 years in accordance with [NZS3602:2003](#), Table 1.

The cavity battens are manufactured from NZ grown Radiata pine and four options are supplied,

- JSC-U 45 x 20 mm universal non-structural cavity battens,
- JSC-V 45 x 45 mm vertical structural cavity battens,
- JSC-H 45 x 45 mm horizontal structural cavity battens, and
- JSC-U 70 x 45 mm universal structural cavity battens.

The 45mm thick structural cavity battens, when structurally fixed to the frame, have sufficient structural integrity to allow the cladding to be fixed directly to the cavity batten. Penetration to the framing is not required. Refer to [JSC Structural Cavity Batten Fixing Guide](#) for fixing requirements.

When using the 20mm non-structural cavity battens, the cladding itself must be structurally fixed to the framing.

JSC cavity battens are intended for use as a component of JSC Codemarked cladding systems.

JSC is the trading name of [J Scott & Company](#).

The company has been FSC certified since 2009. Certificate number [SGSHK-COC 006734](#).

CONTRIBUTION TO BUILDING WORK CODE OBLIGATIONS

JSC cavity battens comply with,

- B1 (Structure): B1.3.1, B1.3.2, B1.3.3 (b, c, q)
- B2 (Durability): B2.3.1 (a)
- F2 (Hazardous Building Materials): F2.3.1

When used in conjunction with an external cladding and in accordance with the cladding suppliers requirements, JSC cavity battens will contribute to compliance with,

- E2 (External Moisture): E2.3.5, E2.3.6, E2.3.7

FOR FURTHER INFORMATION

JSC cavity battens must be used in accordance with JSC Cladding System requirements.

For installation guidance refer to www.JSC.co.nz.

RESPONSIBLE PERSON

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm the JSC cavity battens as referred to in this statement, are not subject to a warning or ban under [s26 of the Building Act](#).

Signed for and on behalf [J Scott & Company Ltd t/a JSC](#):

Martin Hunt

Martin Hunt

COMPLIANCE MANAGER

September 2024