


# SAMBARA

*Triplochiton scleroxylon*



PREMIUM ARCHITECTURAL  
& BUILDING SOLUTIONS

## A perfect choice for interior applications



Ideal for detailed  
interior profiles



Lightweight



Light colour that  
stains very well

Sambara (African whitewood) is a lightweight West African hardwood commonly selected for interior joinery and lining where a consistent, light coloured warm appearance is desired. It machines easily and takes paint, stain, and clear finishes well, making it a versatile choice for interior panelling, ceilings, battens, mouldings, and general fit-out work.

Typically cream to straw in colour with little distinction between sapwood and heartwood, Sambara has a medium texture with natural grain variation that may present as subtle figuring or ribboning.



Sambara coated in JSC Coda Lux Wax (White, Brown, & Black)

## SAMBARA APPLICATIONS

Sambara works well with hand and machine tools and is suited to interior applications such as:

- Interior joinery
- Interior wall panelling & ceilings
- Feature battens
- Compatible with the JSC Clipp Batten System
- Mouldings / trims

## TECHNICAL INFORMATION

<b>Supplier responsibility status</b>	FSC® 100% Certified
<b>Availability of sizes</b>	Lengths: 1.8m – 4.8m Thickness: Commonly available in 25mm & 50mm Width: 100mm, 150mm, & 200mm
<b>Durability</b>	Class 4* - For interior use only
<b>Grades</b>	Clears

\*Durability classifications provide a useful comparative guide, however factors relating to specific installations and natural timber variation may result in heartwood pieces falling outside the species' durability classification.

Mechanical properties	Green	Dry
Modulus of Rupture (MPa)	37 MPa	55–61 MPa
Modulus of Elasticity (GPa)	4.55 GPa	5.52–6.48 GPa
Hardness   Janka (kN)	1.87 kN	1.91 kN
*Density (kg/m3) *Air dry density (kg/m3) is average indication only and actual value may vary.	-	*380 kg/m <sup>3</sup>

**Note:** For comparable species speak to the JSC team about alternatives.

**Disclaimer:** The timber properties and product information provided in this document are intended as general guidelines only. Actual timber characteristics may vary due to origin, growth conditions, environmental influences, and natural variation. JSC has not conducted specific testing on the timber properties referenced; all figures are indicative only and have been sourced from external references cited within this document. Information relating to JSC products is necessarily general in nature and subject to variation in dimension, appearance, and specification, depending on natural factors, installation methods, or the specific application. Customers must independently verify all technical data and obtain professional advice to determine the suitability of any product for their particular purpose. The Customer is solely responsible for ensuring that the product is appropriate for its intended use. JSC does not accept any liability (including for negligence) for claims arising from reliance on this information, documentation, or other related materials.



The mark of responsible forestry  
FSC® C003608

**jsc.co.nz**

TechHelp@jsc.co.nz

Sales@jsc.co.nz

FIND JSC ONLINE



### AUCKLAND

(09) 412 2800  
22 Sawmill Road  
Riverhead

### HAMILTON

0800 57 26 88  
43 McKee Street  
Pukete

### WELLINGTON

0800 57 26 88  
61 Seaview Road  
Seaview

### CHRISTCHURCH

(03) 348 9726  
23 William Lewis Drive  
Sockburn



PREMIUM ARCHITECTURAL  
& BUILDING SOLUTIONS